

Calidus 标准型配置



编号	描述	
41474	CALIDUS 914 UL - China <ul style="list-style-type: none"> - Dual Seat Gyro in tandem configuration - with dual control-option - 4 luggage compartments with covers - Mast and keel stainless steel e-polished - Aluminium rotor system II 8,4m TOPP, Naca 8H12 - Rotor bag - Exhaust stainless steel with after muffler - HTC 3B CCW 172,5 Propeller - Instrument panel <ul style="list-style-type: none"> - Airspeed in km/h and altimeter mbar - Engine and rotor rpm - Oil- and coolant temperature - Oilpressure - Standardcompass Silva - Engine hour meter - Electrical fuel gauge - Pneumatic trim (pitch) and rotor brake - Pneumatic roll trim incl. display in cockpit - Pneumatic rotor pre-rotator with safety interlocks - Hydraulic mainwheels brakes with parking brake - Fuel tank, capacity 39 Ltr. - Additional fuel tank 34 Ltr. - Filler cap lockable - ACL/NAV AutoGyro - Wheel spats rear - Road wheels - All composite parts are painted - Colour choice on colour palette - Pilot-seat with adjustable back, Sitting position and angle - Recommended body height 165-200 cm - Floor mat black - Storage bag backrest - Fully assembled and test flown - Basic price without engine, prepared for Rotax 914 UL 	Calidus 914 UL 中国标准机体 <ul style="list-style-type: none"> - 双座串座自转旋翼机 - 可选双飞行杆 - 4个带盖行李隔间 - 不锈钢电镀主梁及龙骨 - 第二代铝制旋翼系统：8.4米 TOPP，Naca 8H12 - 旋翼固定套 - 不锈钢排气管，铝制二级消声器 - 螺旋桨：HTC 3B CCW 172.5 - 仪表盘 <ul style="list-style-type: none"> - 空速表：km/h；高度表：ft mbar - 发动机及旋翼转速表 - 滑油及冷却液温度表 - 滑油压力表 - Silva标准罗盘 - 发动机小时计 - 电子燃油表 - 气动配平（俯仰）及旋翼刹车 - 气动横滚配平，仪表盘显示 - 气动预旋，自带安全联锁 - 液压主轮刹车及停车刹车 - 燃油箱，39升容量 - 第二油箱，34升容量 - 可锁油箱盖 - AutoGyro导航频闪灯 - 后轮整流罩 - 公路轮胎 - 所有复合材料均上漆 - 颜色可按色卡选择 - 飞行员座椅可调节椅背、座椅位置及角度 - 建议身高为 165-200 cm - 黑色地垫 - 座椅靠背储存包 - 全组装并经试飞 - 不含发动机基础价格，适用于Rotax 914 UL
	500kg suspension bow	500公斤起落架
	Add on nosewheel reinforced 8PR	前轮加强轮胎 8PR（8层）
1196	Motor Rotax 914 UL configured AutoGyro	Rotax 914 UL 发动机，AutoGyro配置
1342	Spinner HTC-prop	HTC螺旋桨桨毂整流罩
1221	Cockpitpanel for Garmin 695/795	仪表盘板，适用于 Garmin695/795
1436	Cover plate GPS Garmin 695/795	盖板：适用于 Garmin695/795
1312	Comfortstick position S	舒适型飞行杆，小号位置
1402	Vertical speed indicator 57 mm in m/s	升速表：直径57mm，单位 ft/min
1295	Additional ventilation window rear	后透气窗口
1313	Interior heating Calidus	Calidus机舱取暖系统
1115	Radio ATR833-LCD, Funkwerk	电台：Funkwerk ATR833-LCD
1122	wiring harness for Radio ATR833	ATR833电台线束
1123	radio antenna	电台天线
1183	LED Landing light	LED 着陆灯
1089	Solid Paint	机身颜色：标准纯色油漆

Calidus 标准型配置



编号	描述	
1240	keel tube fin,	龙骨翅片
1037	Front wheel spat	前轮整流罩
1719	AutoGyro logo grey	AutoGyro 灰色 logo
1024	Calidus logo gr	Calidus: 灰色
1360	Power plug 12V front	前电源插座 12V
1353	Battery charger CTEK	CTEK电池充电器
1258	Instructor pack Calidus incl. installation	教练套装（后座飞行套装）
1416	preparation for loading , wheels off	装柜准备: 拆除轮胎
1415	preparation for loading , Rotor disassembly	装柜准备: 拆卸旋翼系统
1413	load and strap gyro in container / lorry	装柜固定
1407	Box for rotorblades 8,8	旋翼储存盒 8.8m

